



1019.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- **INTEL® Atom Processor D510 / D525 + ICH8M Chipset**
- Support INTEL® Atom Processor D510 / D525(Dual Core) CPU Socket
- Support Single Channel DDR2 800
- **Support CPU Smart FAN**
- Integrated LVDS support 18-bit TFT LCD
- Supports 1x Gigabit LAN
- **Supports ACPI S3 Function**
- Support Watch dog Technology
- Mini-ITX Form Factor(17cm x 17cm)
- CPU
 - INTEL® Atom Processor D510 / D525(Dual Core)
- Chipset
 - INTEL® Atom Processor D510 / D525 + ICH8M Chipset
 - Front Side Bus 667MHz
- Memory
 - 2 * DIMMs Sockets for un-buffered Single Channel DDR2 800/667 SDRAM up to 4 GB
- Expansion Slots
 - 1 * PCI slot
 - 1 * MINI PCI-E
- Storage
 - **Embedded INTEL ICH8M Chipset**
 - 3 * Serial ATA2 3Gb/s connectors
 - 1 * Ultra DMA 100 / 66 IDE connector
- Audio
 - Realtek ALC662 6-Channel HD Audio CODEC
- Ethernet LAN
 - Realtek RTL8111DL PCI-E Gigabit Ethernet LAN
- LVDS
 - Onboard 18-bit single channel LVDS connector

- USB
 - Special Features
 - Rear Panel I / O
 - Internal I / O
 - BIOS
 - Functional
 - Form Factor
- Embedded 9 * USB 2.0/1.1
 - Support ACPI S3
 - Support CPU Smart FAN
 - Support Watch Dog
 - 5 * USB 2.0/1.1 ports
 - 1 * PS2/KB Connector
 - 1 * RJ-45 port
 - 1 * COM port
 - 1 * VGA port
 - 1 * E-SATA Port
 - 1 * 12V DC in
 - 3 * Audio Phone Jack
 - 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
 - 1 * JWDB pin Power connector
 - CPU / NB / Chassis Fan connectors;
 - 1 * 32-pin LVDS headers & 1 * GPIO header & 1 Parallel headers
 - 1 * COM header (COM1 for RS-422/485)
 - 1 * AUDIO header
 - Award 8MB DIP Flash ROM
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
 - Mini ITX Form Factor(17cmx17cm)

Product Accessories

- SATA power cable
- Manual
- CD
- 2x SATA cable
- I/O shield