



469.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Quad-Channel !
- Extended Temperature !
- -40 to 85°C !

**Support:**  [Specifications](#)

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to four channels from multiple composite input sources, reducing system costs. DarkCrystal SD Capture Mini-PCIe Quad makes use of exclusive hardware design guarantying fast response and solid performance for high-density SD capture or encoding demands.

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to 4 channels from multiple composite input sources, reducing system costs.

- Supports extended operating temperatures from -40 to 85°C
- Video capture with composite input
- 4-channel concurrent capture solution
- Standard minicard dimension
- Mainstream programming languages supported
- DirectShow compatible

**Module Type**

**PCI Express Minicard**

**Input**

**4-ch Composite**

**Audio(L/R)**

**Video Resolution**

**NTSC (29.97Hz): 720 x 480, 640 x 480, 360 x 240, 320 x 240, 180 x 120, 160 x 120**

**Color Adjustment**

**PAL (25Hz): 720 x 576, 640 x 480, 360 x 288, 180 x 144**

**Operating Environment**

**Brightness, Contrast, Hue (NTSC only), Saturation**

**Temperature: -40 to +85 ■**

**Humidity: 0 to 90% RHNC**

**Storage Environment****Temperature: -50 to +85 ■****Humidity: 0 to 90% RHNC****1.13W****50.95 x 30mm****Power Requirement****Dimensions (L x W)****CPU****Intel® Pentium®4 3.0 GHz****Memory****AMD AthlonTM 64 3200+****VGA****512 MB RAM****Sound Card****VGA card with support for DirectX9.0c or above****Supported OS****Yes****Windows 7/8.1/10 (32/64 bits), Linux (32/64 bits)\*****System Requirements**