



1669.00 EUR
incl. 19% VAT, plus [shipping](#)

- NVidia Jetson Orin NX!
- Support Super Mode !
- 8GB !

- Applies to NVIDIA® Jetson Orin™ NX module
- Support Super Mode
- 2 x GbE RJ-45 (Optional: Ethernet 2 can be used with OOB for RMII function)
- 1 x OOB for Power cycling and Cloud serial console (Optional)
- 1 x 5G daughter board for 4G/5G functions (Optional)
- 2 x USB 3.2 & 1 x HDMI output
- 2 x M.2 key for SSD/wifi
- 20-pin expansion header
- Operating temperature: -25°C ~ 60°C (TBD)

AVerMedia's D133SOXB Box PC equips powerful NVIDIA® Jetson Orin™ NX modules. This efficient system-on-module (SoM) opens new worlds of embedded IoT applications with full analytic capabilities

D133SOXB Box PC is designed for the industry applications with spatial concern and compact yet efficient for rapid AI-based solution development and seamless deployment as required by demanding business applications.

AVerMedia supports businesses of all sizes and offers customizable BSP services, flexible MoQ, in addition to NVIDIA's JetPack™ SDK.

Model Type	D133SOXB-8G Box PC
NVIDIA GPU SoC Module Compatibility	NVIDIA® Jetson Orin NX 8G
Networking	1 x GbE RJ-45 1 x M.2. key E 2230 for wifi
Display Output	1 x HDMI output 3840 x 2160 at 60Hz for Orin NX Operating temperature -25°C~60°C (TBD)
Temperature	Storage temperature -40°C ~ 85°C Relative humidity 40 °C @ 95%, Non-Condensing
MIPI Camera Inputs(Internal)	2 x 4 lane MIPI CSI-2, 22 pin FPC 0.5mm Pitch
USB	1 x USB 2.0 type C for recovery 2 x USB 3.0 Type-A
Storage	1x M.2. key M 2280 for NVMe (256G SSD installed)
Expansion Header	20 pins: 2x I2C, 1x UART, 9x GPIOs

Security	TPM 2.0 supported
Input Power	3.5mm Screw Terminal; 12V/5A, 9V~24V is recommended.
Power Cord	US/JP/EU/UK/TW/AU/CN
Thermal solution	Fan solution
Buttons	Power and Recovery
RTC Battery	Support RTC battery and Battery Life Monitoring by MCU
Dimension/Weight	W: 93mm x L: 81.2mm x H: 74.4mm (TBD)
Certifications	Weight: 500g (TBD)
Package	CE, FCC, KC(TBA)
	1x Box PC
	12V power adapter/Power cord